

TEST DATA



Load: CHO-0006A HV Power Supply: CHP-1214A Ambient Temperature: 25 degrees C Relative Humidity: 50% Input Voltage: 24V DC


Input Current	Output Voltage	Frequency
1.45A max.	3.86KVrms (10.81KVpp)	16.3KHz
0.65A min.	3.59KVrms (10.00KVpp)	15.8KHz

Notes:

1. CHO-0006A Ozone Cell

Feed gas: dry air (less than 10% RH) or pure oxygen
Feed gas temperature: less than 25 degrees C to extend the life of the product
Feed gas pressure: less than 1kg/cm² to prevent load from being damaged or broken
Ozone cell outlet pressure: lower than 0.2kg/cm² to prevent overpressure situations from occurring inside the ozone cell which could result in a lower ozone production or none ozone production. (* The outlet pressure could be influenced when connecting to an air stone, or when pipe choking occurs.)
(Please refer to image 1)

- 2. CHP-1214A and CHO-0006A: the heat sinks must be kept less than 50 degrees C. It is recommended to install an appropriate cooling fan.
- 3. Warranty of CHP-1214A and CHO-0006A: 1 year. This warranty does not include damage caused by abuse, misuse, or by acts of vandalism.



CHO-0006A & CHP-1214A

